



PRODUCT SPEC SHEET
R2-5MPSPDME

3-inch 5MP Active Deterrence IP PTZ Camera

2880x1620, 5x Optical Zoom



The R2-5MPSPDME is a 5MP (2880x1620) PTZ camera constructed with a 5x module and provides HD image quality.

OPTIONAL SERVICES*

Integrate with Capture Cloud Service, powered by Eagle Eye*

Connect with Capture Remote Monitoring Service (R2-B12SUBK)*

**Require monthly/annual subscriptions*

FEATURES

- 1/2.7" PROGRESSIVE SCAN CMOS, 5MP(2880×1620) @ 25/30FPS
- 5X OPTICAL ZOOM, 16X DIGITAL ZOOM
- FACE, HUMAN AND VEHICLE DETECTION AND CAPTURE
- SMOKE AND FIRE DETECTION AS WELL AS SMART MOTION DETECTION
- AUTO TRACKING AND PERIMETER PROTECTION BASED ON DEEP LEARNING
- INTELLIGENT ANALYSIS: INTRUSION, LINE CROSSING, LOITERING, WRONG-WAY, ILLEGAL PARKING AND PEOPLE COUNTING
- SMART DUAL ILLUMINATION, UP TO 50 M IR AND 30 M WARM LIGHT DISTANCE
- BUILT-IN SD CARD SLOT, UP TO 256GB
- IP66
- PART #: R2-5MPSPDME
- UPC: 840049310322
- DIMENSIONS: 6.87×5.46×10.67 INCH
- WEIGHT: 1.28 KG (2.82 LB)



FOR MORE INFORMATION, CONTACT YOUR ADI SALES PERSON.

CAMERA

IMAGE SENSOR	1/2.7" PROGRESSIVE SCAN CMOS
MAX. RESOLUTION	2880(H)×1620(V)
ELECTRONIC SHUTTER	AUTO/MANUAL, 1/5- 1/20,000S
MIN. ILLUMINATION	COLOR: 0.01 LUX @ (F1.6, AGC ON) B/W: 0.001 LUX @ (F1.6, AGC ON), 0 LUX WITH LIGHT
DAY & NIGHT	IR CUT FILTER
ILLUMINATION DISTANCE	IR DISTANCE UP TO 50 M (164.0 FT) WARM LIGHTS DISTANCE UP TO 30 M (98.4 FT)
ILLUMINATOR ON/OFF CONTROL	AUTO/MANUAL

LENS

FOCAL LENGTH	2.7 TO 13.5MM
MAX. APERTURE	F1.66 ~ F3.03
ANGLE OF VIEW	H: 111.5° TO 32.3°, V: 57.5° TO 17.9°
OPTICAL ZOOM	5X
DIGITAL ZOOM	16X
FOCUS CONTROL	AUTO/MANUAL/SEMI-AUTOMATIC

PTZ

PAN/TILT RANGE	PAN: 0° TO 355° ENDLESS, TILT: -20° TO +90°
PAN SPEED	PAN SPEED: 0.1° TO 60°/S, PRESET SPEED: 60°/S
TILT SPEED	TILT SPEED: 0.1° TO 50°/S, PRESET SPEED: 50°/S
PRESETS	400
PTZ MODE	6 TRACK, 12 SCAN, 12 PATROL (UP TO 32 PRESETS PER PATROL)
POWER-OFF MEMORY	SUPPORT
3D POSITIONING	SUPPORT

PTZ STATUS DISPLAY	SUPPORT
IDLE MOTION	THE TIME CAN BE SET (1-240 MINUTES), AND FUNCTIONS SUCH AS PRESET POSITIONS, PATROLS, SCANS, AND TRACKS CAN BE RUN.

VIDEO

STREAMING CAPABILITY	3 STREAMS
STREAM/FRAME RATE	STREAM1: 2880×1620, 2560×1440, 2304×1296, 1920×1080, 1280×720 @ 25/30FPS STREAM2: D1, VGA, 640×360, CIF, QVGA @ 25/30FPS STREAM3: VGA, CIF, QVGA @ 25/30FPS
BIT RATE CONTROL	CBR/VBR
BIT RATE	STREAM1: 200KBPS-12MBPS STREAM2: 100KBPS-6MBPS STREAM3: 100KBPS-3MBPS
SMART ENCODER	SUPPORT
REGION OF INTEREST (ROI)	SUPPORT

IMAGE

IMAGE ADJUSTMENT	BRIGHTNESS, SHARPNESS, CONTRAST, SATURATION
MIRROR	SUPPORT
EXPOSURE MODE	AUTO/MANUAL
WHITE BALANCE	AUTO/MANUAL
DAY/NIGHT SETTING	AUTO, DAY, NIGHT, TIME
SMART ILLUMINATION	SUPPORT
NOISE REDUCTION	2D/3D DNR
IMAGE ENHANCEMENT	HLC, BLC, DEFOG, ANTI-SHAKE
WIDE DYNAMIC RANGE	TRUE WDR
S/N RATIO	55DB

**FOR MORE INFORMATION,
CONTACT YOUR ADI SALES PERSON.**

MOTION DETECTION	SUPPORT
PRIVACY MASKING	SUPPORT 40 ZONES, MASK COLOR CONFIGURABLE
AUDIO	
COMPRESSION	G.711: 8KBPS, RAW_PCM: 16KBPS
SMART FUNCTION	
MULTI-OBJECT DETECTION	SUPPORT FACE, HUMAN, VEHICLE DETECTION AND CAPTURE
INTELLIGENT ANALYSIS	INTRUSION, SINGLE LINE CROSSING, DOUBLE LINE CROSSING, LOITERING, WRONG-WAY, ILLEGAL PARKING, (SUPPORT THE ACCURATE DETECTION OF VEHICLE AND HUMAN)
SMOKE AND FIRE DETECTION	SUPPORT
PEOPLE COUNTING	SUPPORT
SMART MOTION DETECTION	SUPPORT
SMART TRACKING	SUPPORT
ACTIVE DETERRENCE	
LIGHT WARNING	RED AND BLUE LIGHT WARNING FLASH FREQUENCY: HIGH, MEDIUM, LOW
SOUND WARNING	SOUND WARNING ALARM: CUSTOMIZABLE VOICE AND ALARM SOUNDS
NETWORK	
PROTOCOLS	IPV4, IPV6, TCP/IP, HTTP, HTTPS, UPNP, RTSP/RTP/RTCP, IGMP/MULTICAST, SMTP, DHCP, NTP, DNS, QOS, SNMP, 802.1X, UDP, ICMP, ARP, TLS
INTEROPERABILITY	ONVIF, SDK, CGI
STREAMING METHOD	MULTICAST
MAX. USER ACCESS	10 USERS
WEB VIEWER	<IE11, CHROME, FIREFOX, MICROSOFT EDGE

LANGUAGE	ENGLISH, CHINESE, POLISH, ITALIAN, PORTUGUESE, SPANISH, RUSSIAN, FRENCH, CZECH, HUNGARIAN. DEFAULT: ENGLISH
INTERFACE	
NETWORK INTERFACE	1 ETHERNET (10/100 BASE-T) RJ-45 CONNECTOR
BUILT-IN MICROPHONE	SUPPORT
BUILT-IN SPEAKER	SUPPORT, MAX SOUND TRANSMISSION DISTANCE OF 60 M (196.85 FT) (45-48 DB)
ALARM INTERFACE	1CH INPUT, 1CH OUTPUT
SD CARD SLOT	BUILT-IN, UP TO 256GB
RESET BUTTON	BUILT-IN
ELECTRICAL	
POWER SUPPLY	DC12V/POE+ (IEEE 802.3AT)
POWER CONSUMPTION	LESS THAN 19.5 W (ILLUMINATOR + RED AND BLUE WARNING LIGHT + SPEAKER + PTZ WORKING + GLASS DEFOGGING)
OPERATING TEMPERATURE	-30°C TO 60°C (-22°F TO 140 °F)
OPERATING HUMIDITY	LESS THAN 90% RH
INGRESS PROTECTION	IP66
CERTIFICATIONS	CE/FCC
CASING	METAL + PLASTIC
DIMENSIONS	174.4×138.8×270.9 MM (6.87×5.46×10.67 INCH) OF WALL MOUNT
NET WEIGHT	1.28 KG (2.82 LB)

**FOR MORE INFORMATION,
CONTACT YOUR ADI SALES PERSON.**